

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65B 11/50	A1	(11) International Publication Number: WO 00/55044 (43) International Publication Date: 21 September 2000 (21.09.00)
(21) International Application Number: PCT/EP00/01647 (22) International Filing Date: 29 February 2000 (29.02.00) (30) Priority Data: 9906179.8 17 March 1999 (17.03.99) GB (71) Applicant (for AE AU BB CA CY GB GD GH GM IE IL KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG ZA ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). (71) Applicant (for all designated States except AE AU BB CA CY GB GD GH GM IE IL IN KE LC LK LS MN MW NZ SD SG SL SZ TT TZ UG ZA ZW): UNILEVER NV [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL). (71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN). (72) Inventor: HARBOUR, Richard; Lever Brothers Ltd, P.O. Box 69, Port Sunlight, Wirral, Merseyside CH62 4ZD (GB).		(74) Agents: ELLIOTT, Peter, William et al.; Unilever PLC, Patent Department, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB). (81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: A PROCESS FOR PRODUCING A WATER SOLUBLE PACKAGE (57) Abstract <p>A process for producing a thermoformed package comprises the steps of placing a first sheet of film over a forming die having at least one cavity; heating the film to mould the film into the at least one cavity thereby forming at least one recess in the film, placing a composition in the at least one formed recess and sealing a second sheet of film across the at least one formed recess to produce at least one closed package. Each cavity includes a curved edge at least a portion of which comprises a resiliently deformable material.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

A PROCESS FOR PRODUCING A WATER SOLUBLE PACKAGE

The invention relates to a process for producing a
5 thermoformed package of the type comprising the steps of
placing a first sheet of formable film over a forming die
having a cavity; moulding the film into the cavity thereby
forming a recess in the film, placing a composition in the
thus formed recess, and sealing a second sheet of film
10 across the recess to close the package. In particular, the
invention relates to such a process for producing a water-
soluble package containing a detergent composition.

Detergent compositions for the machine washing of laundry
15 are provided in many forms. Probably the most prevalent form
of laundry detergent is washing powder or granules. A
problem with the use of these forms of detergent is that the
product needs to be dosed into the machine in such a way
that the detergent is quickly and thoroughly dissolved in
20 the wash water of the machine without coming into contact
with the laundry in a solid form. In this regard many dosing
devices which overcome this problem have been proposed. One
such device disclosed in European Patent Nos. 0 343 070 and
0 343 069 teaches the use of a flexible fabric sock which
25 holds the particulate detergent in the machine, the fabric
of the sock being permeable to water so as to allow water
enter the sock and carry the detergent out of the sock
through the fabric walls in the form of an aqueous solution.
More recently unit dose forms of detergent have been
30 proposed in the form of compressed tablets of detergent
powder. A problem encountered with the provision of
detergent tablets is that the tablets need to be strong
enough to withstand storage and transport, yet weak enough
to disintegrate and dissolve quickly in the washing machine.
35 A further problem is the need to prevent the tablets
"posting" in the porthole and between the drums of

- 2 -

conventional washing machines. More recently these problems have been overcome by the provision of detergent tablets having specific chemical disintegrants which allow quick disintegration of the tablets in the aqueous environment of a washing machine, and by the provision of loosely fitting net bags which aid tablet disintegration and prevent "posting". However, as many of the current detergent tablets contain bleach and other irritant substances, the problem of handling the tablets remains.

The provision of detergent compositions in water-soluble films has been known for some time. Most of the documents relating to this subject describe water soluble film envelopes formed using a vertical form-fill-seal (VFFS) route. A problem with envelopes produced using this VFFS method is that, due to the constraints of the process, the resultant envelopes have seals which incorporate defined weak points where the seals overlap at corners. This results in envelopes, which are easily corrupted as a result of impacts suffered during transport. In an attempt to overcome the problems associated with such VFFS envelopes, European Patent Application No. 0 608 910 describes thermoformed water soluble packages for pesticidal compositions of the above mentioned type, which packages include a seal which does not have any angular intersections with itself. While this specification does provide a partial solution to the problem of weak seals, the thermoforming of water-soluble films results in formed packages having many other weak points. Moreover, the packaging and transport of such packages subjects the formed packages to considerable impact forces.

It is an object of the invention to overcome at least some of the above problems

- 3 -

Statements of Invention

According to the invention, there is provided a process for producing a thermoformed package of the above mentioned
5 type, the process being characterised in that the or each cavity in the forming die has a curved edge, wherein at least a portion of the curved edge is formed from a material which is less hard and more deformable than the material of the cavity. Ideally, at least a portion of the
10 curved edge comprises a resiliently deformable material. Generally, a predominant portion, and most preferably a whole, of the curved edge is formed of a resiliently deformable material. In one embodiment of the invention, the curved edge comprises an annular gasket of resiliently
15 deformable material, which gasket is mounted in a circumferential groove around the or each cavity. In such a case, the gasket should be dimensioned such that, when mounted in the groove, an exposed surface of the gasket should be flush with a surface of the cavity.

20 In a further aspect of the invention, the or each cavity is surrounded by a raised flange, wherein at least a portion, and ideally most or all, of the raised flange comprises resiliently deformable material. In such a case, the curved
25 edge and flange are preferably integrally formed. Thus, a single gasket preferably comprises the curved edge and the flange. In one embodiment of the invention, a ratio of a width of the flange to a minor diameter of the cavity is between 1:50 and 1:10, preferably about 1:12.

30 The resiliently deformable material is preferably silicone rubber, however other suitable material performing the same function are envisaged.

- 4 -

In the thermoforming step of the process of the invention, the film is heated by a heating plate. This may be flat but preferably has at least one concave depression which in use overlies the at least one cavity, wherein the heating step
5 involves the step of bringing the film into intimate contact with the or each depression. The use of a heating plate having concave depressions helps to ensure that the film when heated thermoforms uniformly which results in a package having less weak spots.

10

In one embodiment of the invention, intimate contact between the film and the concave depression is achieved by exerting a vacuum between the depression and the film. In this regard the depression may include holes through which the vacuum
15 may be pulled. Alternatively, the heating plate may comprise a porous material. When a vacuum is exerted in this manner, the vacuum should ideally comprise a pressure of up to 1 Bar, and preferably be less than 0.6 Bar. In an alternative embodiment of the invention, the film is forced into
20 intimate contact with the concave depression by blowing air against it. Typically the pressure of the blown air will be less than 5 Bar, preferably less than 3 Bar. The heating plate preferably has a temperature in the region of 100 to 120 degrees C, and ideally is approximately 110 degrees C.
25 Although the time the film contacts the heating plate depends to a large extent on the type of film used and the temperature of the heating plate, the time of contact between the film and the plate should be in the region 0.1 to 5 seconds, preferably 0.5 to 1 seconds, ideally
30 approximately 700 milliseconds.

In one embodiment of the invention the film is a water-soluble film. Ideally the package contains a liquid, gel or other type of fluent composition. Preferably, the liquid
35 comprises a detergent or any other type of active agent used

- 5 -

in the machine washing of laundry or dishes. In another embodiment of the invention, the package contains a bathing or shower gel composition or any other type of personal care composition.

5

Detailed Description of the Invention

The invention will be more clearly understood from the following description of an embodiment thereof, given by way
10 of example only, with reference to the accompanying drawings in which:-

Fig 1 is a sectional view illustration portions of a forming die and heating plate for use with the process of the
15 invention;

Fig 2 is a detailed sectional view of a concave depression of Fig 1; and

20 Fig 3 is a detailed sectional view of an edge of a forming cavity according to the invention.

EXAMPLE

25 In this example a thermoforming process is described where a number of packages according to the invention are produced from a sheet of water soluble material, namely polyvinyl alcohol supplied under reference CC8534 from Chris Craft. In this regard recesses are formed in the sheet using a forming
30 die having a plurality of cavities with dimensions corresponding generally to the dimensions of the packages to be produced. Further, a single heating plate is used for moulding the film for all the cavities, and in the same way a single sealing plate is described.

35

- 6 -

A first sheet of polyvinyl alcohol film is drawn over a forming die so that the film is placed over the plurality of forming cavities in the die, the details of which are described in further detail below. In order to maximise package strength, the film is delivered to the forming die in a crease free form and with minimum tension.

In the forming step, and referring to Figs 1 and 2, the film is heated to 110 degrees C, for approximately 700 micro seconds. A heating plate 1 is used to heat the film, which plate is positioned to superpose the forming die 2. The plate includes a plurality concave depressions 3 (only one is shown) which correspond to the cavity 4 on the forming die 2. Each concave depression is generally circular having a diameter of approximately 50mm and a depth of about 5mm. An edge 5 of the depression 3 is radiussed as is the base 6, the radius of the base being about 50mm and the radius of the edge being about 30 mm. During this preheating step, a vacuum is pulled through the pre-heating plate to ensure intimate contact between the film and the pre-heating plate 1, this intimate contact ensuring that the film is heated evenly and uniformly (the extent of the vacuum is dependant of the thermoforming conditions and the type of film used, however in the present context a vacuum of less than 0.6 bar was found to be suitable) Non-uniform heating results in a formed package having weak spots. As an alternative, or in addition, to the vacuum, it is possible to blow air against the film to force it into intimate contact with the preheating plate. In such cases the air should be blown at a pressure of less than 3 Bar.

The thermoformed film is thus moulded into the cavities forming a plurality of recesses which, once formed, are retained in their thermoformed orientation by the application of a vacuum through the walls of the cavities.

- 7 -

This vacuum is maintained at least until the packages are sealed. Once the recesses are formed and held in position by the vacuum, the composition, in this case a liquid detergent is added to each of the recesses. A second sheet of
5 polyvinyl alcohol film is then superposed on the first sheet covering the filled recesses and heatsealed thereto using a heating plate. In this case the heat sealing plate, which is flat, operates at a temperature of about 140 to 160 degrees centigrade, and contacts the films for 1 to 2 seconds and
10 with a force of 8 to 30kg/cm², preferably 10 to 20kg/cm².

In more detail, and referring to Fig 3, each cavity 4 is generally dome shaped having a curved edge 10 with a radius of curvature. A raised flange 11 surrounds each cavity to
15 ensure that the films are sealed together along the flange to form a continuous seal. In this embodiment, the radiussed edge 10 and raised flange 11 are both formed by a resiliently deformable material gasket 12 of silicone rubber. This results in reduced force being applied at the
20 inner edge of the sealing flange to avoid heat/pressure damage to the film.

Once sealed, the packages formed are separated from the web of sheet film using cutting means. At this stage it is
25 possible to release the vacuum on the die, and eject the formed packages from the forming die. In this way the packages are formed, filled and sealed while nesting in the forming die. In addition they may be cut while in the forming die as well.

30 During the forming, filling and sealing steps of the process, the relative humidity of the atmosphere is controlled to ca. 50%. This is done to maintain the heat sealing characteristics of the film. When handling thinner
35 films, it may be necessary to reduce the relative humidity

- 8 -

ensure that the films have a relatively low degree of plasticisation and as such tend to be stiffer resulting in easier handling. The actual specific RH of the atmosphere needed will vary according to the temperature of the environment and the type of film used, however for temperatures in the region of 20 degrees C, the RH should be in the region of 30 to 50% depending on the thickness and elasticity of the film.

- 5
- 10 The invention is not limited to the embodiment hereinbefore described which may be varied in both construction, detail and process step without departing from the process of the invention.

15

CLAIMS

1. A process for producing a thermoformed package comprising the steps of:-
- 5
- placing a first sheet of film over a forming die having at least one cavity;
 - heating the film;

10

 - moulding the film into the at least one cavity thereby forming at least one recess in the film;
 - placing a composition in the at least one formed recess;

15

 - and
 - sealing a second sheet of film across the at least one formed recess to produce at least one closed package,

20

 - the process being characterised in that the or each cavity in the forming die has a curved edge, wherein at least a portion of the curved edge is formed from a resiliently deformable material.
- 25
2. A process as claimed in claim 1 in which a predominant portion of the curved edge is formed of a resiliently deformable material.
- 30
3. A process as claimed in claims 1 or 2 in which the curved edge comprises an annular gasket of resiliently deformable material, which gasket is mounted in a circumferential groove around the or each cavity.

- 10 -

4. A process as claimed in any preceding claim in which the resiliently deformable material comprises silicone rubber.
- 5 5. A process as claimed in any proceeding claim in which the or each cavity is surrounded by a raised flange, wherein at least a portion of the raised flange comprises resiliently deformable material.
- 10 6. A process as claimed in claim 5 in which a predominant amount of the raised flange comprises resiliently deformable material.
- 15 7. A process as claimed in any of claims 5 or 6 in which a ratio of a width of the flange to a minor diameter of the cavity is between 1:50 and 1:10, preferably about 1:12.

Fig.1.




Fig.2.





Fig.3.



INTERNATIONAL SEARCH REPORT

Internat'l Application No

PCT/EP 00/01647

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B65B11/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 93 03 456 U (MOSHEER) 29 April 1993 (1993-04-29) page 2, line 29 - page 4, line 20; figures 1-4	1,2,5,6
Y	GB 2 060 544 A (TAKAMURA) 7 May 1981 (1981-05-07)	1,2,5,6
A	page 1, line 77 - line 111; figure 1	3,4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 May 2000

Date of mailing of the international search report

16/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3018

Authorized officer

Claeys, H

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/01647

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 9303456	U	29-04-1993	NONE	
GB 2060544	A	07-05-1981	JP 1247928 C	16-01-1985
			JP 56057613 A	20-05-1981
			JP 59020527 B	14-05-1984
			DE 3038115 A	30-04-1981
			FR 2467779 A	30-04-1981
			US 4398380 A	16-08-1983